

Cylinder trolley specification

A. Single cylinder Trolley for Holding Single Cylinder, Mounting Bracket for Holding Cylinder with Chain & Velcro

Specification:

- 1) Single cylinder hand trolley to transport one no. heavy compressed gas cylinders. (Cylinder size-50, Height-Approx-1400mm, Diameter-236mm, Tare wt-65Kg, Water capacity-50lts, Gas volume-7m³)
- 2) Hand trolley should be fitted with four nos. large solid rubber-tired wheels and castors for better manoeuvrability over rough or even surfaces (2 nos. 8" x 2" Wheels in Front in through shaft & 2 nos. 4" x 2" Castors in the rear).
- 3) Trolleys should be finished with scratch resistant high gloss electrostatically applied oven baked powder coat.
- 4) Material of construction: 18 gauge heavy duty mild steel, White powder coated
- 5) The trolley should be fabricated with 1.25" OD Pipe.
- 6) M.S. Plate is placed on base of the frame on which the cylinder rests.
- 7) Handle is provided for movement & suitably designed clamps / chain are provided to hold the cylinder firmly as per sketch.



B. Double cylinder Trolley for Holding Double Cylinder (compressed gas cylinders) with Toolbox, Cylinder

Mounting Bracket for Holding Cylinder with Chain & Velcro, solid rubber front wheels (Four wheels/ with tool box) Two-cylinder hand trolley (Big Jumbo Type/ 7 cubic meters):

Specification: Two-cylinder hand trolley (Big Jumbo Type/ 7 cubic meters):

- 1) Two-cylinder hand trolley to transport two nos. heavy compressed gas cylinders. (Cylinder size-50, Height-Approx-1400mm, Diameter-236mm, Tare wt-65Kg, Water capacity-50lts, Gas volume-7m³)
- 2) Trolley should be fitted with four nos. large solid rubber-tired wheels and castors for better manoeuvrability over rough or even surfaces (2 nos. 8" x 2" Wheels in Front in through shaft & 2 nos. 4" x 2" Castors in the rear).
- 3) Trolleys should be finished with scratch resistant high gloss electrostatically applied oven baked powder coat.
- 4) Material of construction: 18-gauge HEAVY-DUTY mild steel, White powder coated
- 5) The trolley should be fabricated with 33mm OD Pipe.
- 6) M.S. Plate is placed on base of the frame on which the cylinder rests.
- 7) Handle is provided for movement & suitably designed clamps / chain are provided to hold the cylinder firmly as per sketch.
- 8) 1 No 18 Swag Tool-Tray Type Box (18" x 6" x 4") Specifications:

